


Cat. No.	Insulation Type	TIW Conductor Size Range	Temp Class °C	Rated Volts UL 60950-1 V peak	Rated Volts UL 60601-1 V peak	Rated Volts UL 61800-5-1 V rms
DIWW-B	Supplementary	0.129 - 0.984 mm	130(B)	420	-	-
TIWW-B	Reinforced	36 - 18 AWG	130(B)	1410	-	-
TIWW-B(LZ)	Reinforced	Nominal overall diameter of 0.127 mm-1.02 mm or Cross sectional area 0.0121 mm ² - 0.800 mm ²	130(B)	1410	354	-
TIWW-B(M)+	Reinforced	34 - 18 AWG	130(B)	1410	354	-
DIWW-F	Supplementary	0.129 - 0.984 mm	155(F)	420	-	-
TIWW-F	Reinforced	36 - 18 AWG	155(F)	1410	-	-
TIWW-F(M)+	Reinforced	34 - 18 AWG	155(F)	1410	354	-

+ - This wire has also been investigated using the test voltage for the Electric Strength-twist paired test as described in ANSI AMMI ES60601-1.

Marking: Company name, material designation and the Recognized Component Mark,  on the smallest unit container in which the product is packaged, spool, or on a tag attached to the end of the wire.